DATASHEET - 170M5465

Fuse-link, high speed, 900 A, AC 690 V, size 2, aR, IEC, UL, single indicator

Catalog No. **170M5465**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	900
Rated voltage			AC 690 V
Construction size			size 2
Utilization category			aR
Status indicator			single (top) indicator system
Description			indicator style K for microswitch
Breaking Capacity		kA	200
usable for size/applications			semiconductor protection
Standard/Approval			IEC UL
Shape			square body with flush end contacts
Standards/Regulations			IEC 60269-4

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	900
Rated voltage		V	690
Voltage type			AC
Rated switching capacity		kA	200
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			Other
Insulated metal gripping lugs (IMGL)			No

Additional product information (links)

High-speed full-line catalogue (pdf)	http://www1.cooperbussmann.com/pdf/dc416ece-4392-4b42-ab36-39df6058b353.pdf

© 09/2019 by Eaton Industries GmbH