DATASHEET - 170M8557D

Fuse-link, high speed, 1600 A, AC 690 V, DIN 3, aR, DIN, IEC, dual indicator, live gripping lugs

Catalog No. **170M8557D**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	1600
Rated voltage			AC 690 V
Construction size			DIN 3
Utilization category			aR
Status indicator			dual (combination) indicator system
Description			live gripping lugs indicator style T for microswitch
Breaking Capacity		kA	200
usable for size/applications			semiconductor protection
Standard/Approval			DIN IEC
Shape			square body with knife blade contacts
Standards/Regulations			DIN 43620 IEC 60269-4

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)

Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])

Construction size			Other
Rated current		A	1600
Rated voltage		V	690
Voltage type			AC
Rated switching capacity		kA	200
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			Combination fuse status indicator
Insulated metal gripping lugs (IMGL)			No

Assets (links)

Declaration of CE Conformity

00003191

Additional product information (links)

Product datasheet (pdf)	http://www1.cooperbussmann.com/pdf/ca1a6bc7-bb6b-44a1-9c84-9b553fae7f8c.pdf

© 09/2019 by Eaton Industries GmbH